

## EAST Search History

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L2	7	(radio near3 communication near3 device with transmit\$5 near3 power near3 accord\$5 near3 transmit\$4 near3 power near3 control near3 bit with other near3 station and control\$4 near3 gain near3 variable near3 gain near3 amplifier with transmi\$6 near3 system with set\$4 and detect\$4 transmit\$4 near3 power and calculat\$4 near3 error with comparing transmitted near3 power with transmitted near3 power near3 set\$4 and decid\$3 near3 transmit\$5 near3 power with threshold with above near5 below). clm.	US-PGPUB; USPAT; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/07/05 10:32
L4	0	(switch\$4 with select\$3 near3 output\$4 with error and gain near3 correct\$4 with threshold and error near3 decid\$4 with switch with within near3 tolerance and integrat\$4 near3 output\$3 near3 gain near3 correct\$4 near3 value and add\$5 with set\$4 near3 transmit\$4 near3 power with gain near3 correct\$4 and power near3 gain near3 control\$4 with convert\$3 near3 add\$4 near3 result with control\$5 near3 gain with amplifier). clm.	US-PGPUB; USPAT; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/07/05 10:41
L5	0	2 and 4	US-PGPUB; USPAT; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/07/05 10:42